

COMPRESSOR DATA SHEET
Rotary Compressor: Fixed Speed



MODEL DATA - FOR COMPRESSED AIR

1	Manufacturer: Boge Kompressoren		
2	Model Number: S 150-3	Date:	6/24/2013
	<input checked="" type="checkbox"/> Air-cooled <input type="checkbox"/> Water-cooled	Type:	Screw
	<input checked="" type="checkbox"/> Oil-injected <input type="checkbox"/> Oil-free	# of Stages:	1
3*	Rated Capacity at Full Load Operating Pressure ^{a, e}	682.58	acfm ^{a, e}
4	Full Load Operating Pressure ^b	100	psig ^b
5	Maximum Full Flow Operating Pressure ^c	110	psig ^c
6	Drive Motor Nominal Rating	147	hp
7	Drive Motor Nominal Efficiency	95.0	percent
8	Fan Motor Nominal Rating (if applicable)	8.4	hp
9	Fan Motor Nominal Efficiency	90.2	percent
10*	Total Package Input Power at Zero Flow ^e	25.8	kW ^e
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure ^d	130.1	kW ^d
12*	Specific Package Input Power at Rated Capacity and Full Load Operating Pressure ^e	19.07	kW/100 cfm ^e

* For models that are tested in the CAGI Performance Verification Program, these items are verified by program administrator

Consult CAGI website for a list of participants in the third party verification program: www.cagi.org

NOTES:

- Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; acfm is actual cubic feet per minute at inlet conditions.
- The operating pressure at which the Capacity and Electrical Consumption were measured for this data sheet.
- No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.



Member

Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
<u>m³ / min</u>	<u>ft³ / min</u>	%	%	
Below 0.5	Below 15	+/- 7	+/- 8	+/- 10%
0.5 to 1.5	15 to 50	+/- 6	+/- 7	
1.5 to 15	50 to 500	+/- 5	+/- 6	
Above 15	Above 500	+/- 4	+/- 5	

ROT 031